#### TECHNICAL UNIVERSITY OF MOMBASA

#### DEPARTMENT OF MECHANICAL AND AUTOMOTIVE ENGINEERING

#### **UNIVERSITY EXAMINATIONS 2015/2016**

# FOURTH YEAR FIRST SEMESTER UNIVERSITY EXAMINATION FOR THE DEGREE IN BACHELOR OF SCIENCE IN MECHANICAL ENGINEERING (BSME)

**EMG 2401: INDUSTRIAL HYDRAULICS** 

SERIES: MAY 2016

TIME: 2 HOURS

## **INSTRUCTION TO CANDIDATES:**

- 1. You should have the following for this examination:-
  - Answer Booklet
  - Scientific Calculator
- 2. This paper consists of FIVE Questions
- 3. Question ONE is COMPULSORY
- 4. Answer any other TWO Questions
- Question ONE carries 30 Marks and the other FOUR questions carry 20 Marks each
- 6. All symbols have their usual meaning unless specified otherwise

### **QUESTION ONE:** (COMPULSORY: 30 Marks)

- a) State FIVE (5) advantages of hydraulic systems over other methods of power transmission. (5 Marks)
- b) i) Name two types of hydraulic pump in each of the following categories:
  - Non-Positive Displacement
  - Positive Displacement
  - With the aid of a sketch, explain the operation of a lobe pump. (10 Marks)
- c) A hydraulic system is to be designed for clamping work and to perform drilling operation. The system is to consist of the following components:
  - Reservoir
  - Pump
  - Relief Valve

- Manually operated spring centered three position four way directional control valve.
- Two sequence valves
- Two double acting actuators

Using two line diagram and hydraulic symbols, design and draw a suitable circuit diagram for the system. (15 Marks)

## QUESTION TWO: (20 Marks)

- a) The hose supplying the cylinder operating the bucket of a large excavator has fluid at 1000 psi flowing at 5 gpm. What is the available power in the line?
   (6 Marks)
- b) Hydraulic oil ISO 68 is flowing through a hydraulic line with inside diameter 0.05m at a rate of 300 gpm. Find the pressure drop in psi for a 3m length of hose.

Given: Hydraulic oil ISO 68 has a density of 880 kg/cu-m and a kinematic viscosity of  $6.8 \times 10^{-5}$  m<sup>2</sup>/<sub>s</sub> at 104 F. (6 Marks)

- c) A hydraulic hose with internal diameter of 25 mm is carrying oil with kinematic viscosity of  $5.0 \times 10^{-5} \, m^2 / s$  at a flow rate of 20 gpm. Calculate the Reynolds number and determine if the flow is laminar or turbulent. (3 Marks)
- d) Mention TWO different types of pressure control valves and state their use in a hydraulic system. (2 Marks)
- e) Assisted by a graphical diagram, state the meaning of the following terms as applied to a pressure relief valve:

Cracking pressure (1 Mark)

• Full-flow pressure (1 Mark)

• Pressure over-ride (1 Mark)

## **QUESTION THREE:** (20 Marks)

a) Illustrate the operations of the following types of cylinders as used in hydraulic systems:

- i) Double rod cylinder
- ii) Single acting cylinder with spring.

With the aid of a sketch, explain the construction of a Tie-Rod Cylinder.

(10 Marks)

- b) i) Differentiate a Relief valve from a Sequence valve in pressure control valves.
- ii) Outline the FOUR variables upon which the flow of hydraulic fluid depends on in a Throttle valve. (10 Marks)

## **QUESTION FOUR: (20 Marks)**

- a) There are several hydraulic systems used in the industries. Explain the working principles of the following basic hydraulic systems (use sketches):
  - i) Open Center system

(3 Marks)

ii) Motor Reversing system

(3 Marks)

iii) Closed Center system

(3 Marks)

- b) i) Outline three functions of hydraulic system reservoirs.
  - ii) Explain the principle of operation of the following hydraulic filters.
    - Surface filtration
    - Depth filtration

(6 Marks)

- c) Outline two possible causes and remedies for each of the following trouble in hydraulic system:
  - i) Absence of proper speed and torque of the hydraulic motor.
  - ii) Sudden drop of pressure in the accumulator.

(5 Marks)

# QUESTION FIVE: (20 Marks)

a) A hydraulic hose with internal diameter of 25 mm is carrying oil with kinematic viscosity of  $5.0 \times 10^{-5} \, m^2 / s$  at a flow rate of 20 gpm. Calculate the Reynolds number and determine if the flow is laminar or turbulent. (4 Marks)

- b) Mention TWO different types of pressure control valves and state their use in a hydraulic system. (2 Marks)
- c) i) Differentiate between filters and strainers and name the THREE parts of a Full-flow hydraulic filter and their functions. (4 Marks)
- ii) Describe the structure and operation of a proportional flow filter and state when it can be used. (3 Marks)
- d) i) In addition to flexible hoses, mention TWO other types of hydraulic fluid conductors and give THREE reasons why hoses are the best form of the fluid power plumbing.

  (3 Marks)
- ii) List down FOUR requirements of the fluid power plumbing. (4 Marks)

#### **USEFUL RELATIONSHIPS:**

TABLE 1: Conversion between Pressure Units

	Pascals	Megapascal	Bar	lbs-sq-in
	(Pa)	(MPa)	(Bar)	(Psi)
1 Pa	1	$10^{-6}$	$10^{-5}$	$145 \times 10^{-6}$
1 MPa	$10^{6}$	1	10	145
1 Bar	10 <sup>5</sup>	0.1	1	14.5
1 Psi	6895	$6.895 \times 10^{-3}$	0.06895	1

TABLE 2: Conversion between Volume Flow Rate Units

	gallons/minute	liter/minute	cubicmeter/sec
	(gpm)	(lpm)	$(m^3/s)$
1 gpm	1	3.785	$6.31 \times 10^{-5}$
1 lpm	0.264	1	$1.67 \times 10^{-5}$
$1m^3/s$	$1.585 \times 10^4$	$6 \times 10^{4}$	1