



TECHNICAL UNIVERSITY OF MOMBASA

FACULTY OF ENGINEERING AND TECHNOLOGY

DEPARTMENT BUILDING AND CIVIL ENGINEERING

UNIVERSITY EXAMINATION FOR:

BSC IN CIVIL ENGINEERING

ECE 2402: HYDROLOGY I

END OF SEMESTER EXAMINATION

SERIES: APRIL 2016

TIME: 2 HOURS

DATE: 16 May 2016

Instructions to Candidates

You should have the following for this examination

-Answer Booklet, Drawing Instruments, Scientific calculator, examination pass and student ID

This paper consists of five questions. Attempt question ONE (Compulsory) and any other TWO questions.

Q1. (COMPULSORY)

a) (i) Briefly describe the area velocity method of measuring discharge (6 marks)

(ii) In order to compute the flood discharge in a stream by the slope-area method the following data was obtained.

	Upstream Section	Middle Section	Downstream Section
Area (m ²)	108.6	103.1	99.8
Wetted Perimeter (m)	65.3	60.7	59.4
Gauge reading (m)	316.8	-	316.55

Determine the flood discharge assuming Manning's $n=0.029$ given the length between the upstream and downstream section is 250m. (8 marks)

b) A catchment has the following annual precipitation for six rain gauge stations.

STATION	A	B	C	D	E	F
RAINFALL(mm)	826	1029	1803	11103	988	1367

Determine the required number of optimum rainfall stations in the catchment for precipitation with 10%, 5% and 2% errors. (8 marks)

c) (i) Explain how evaporation can be measured using class A pan.

(ii) Briefly discuss factors that affect translation of evaporation pan measurements to Actual evaporation. (8 marks)

(CHOOSE ANY TWO QUESTIONS)

Q2.

a) Discuss factors affecting evapotranspiration process. (8 marks)

b) State Dalton's law of evaporation and discuss the significance of each parameter in Dalton's equation. (6 marks)

c) Evaluate the actual evaporation, if 10 litres of water is removed from an evaporation pan of diameter 122 mm, to maintain the stipulated water level in the pan. A rainfall of 10mm has been recorded simultaneously. The Pan coefficient is 0.9 for the evaporation pan. (6 marks)

Q3.

- a) (i) Explain stream gauging
(ii) Briefly explain the term 'rating curve' **(6 marks)**
- b) Outline the considerations in selecting a stream gauge station **(6 marks)**

Q4.

- a) Explain two possible types of errors encountered in precipitation data **(4 marks)**


- b) The table below shows the annual precipitation at five stations in a watershed. Data at station A is suspect. Using appropriate means determine the suspect periods. Determine the possible correct 1967 annual precipitation at station A.

	Annual Precipitation for Station (mm/year)				
Year	A	B	C	D	E
1965	894	1016	834	1244	1082
1966	764	840	1114	1048	1076
1967	912	1142	1100	1312	1142
1968	804	1086	884	942	1126

1969	646	988	998	1228	858
1970	1588	996	1696	1450	1510
1971	1258	1050	1302	1090	1308
1972	826	732	890	804	1084
1973	1272	882	982	1134	1234
1974	1036	1130	836	1310	1220
1975	1164	852	962	1074	888
1976	1032	1200	1066	1200	1248
1977	1378	1378	1178	1060	1252
1978	1274	1118	1356	1130	1354
1979	1374	1062	1302	1350	1286
1980	936	938	874	868	1008

(8 marks)

b) Referring to the adjacent figure. The table below shows the normal precipitation for the month of August at eleven gauges in a flat interior watershed. During a storm event which occurred on August 15, 2015, gauge D failed. Estimate the most likely the precipitation at gauge D during the storm event in mm /day giving reasons for any assumptions made.

	August normal precipitation mm/month	August 17, 2006 precipitation in mm/day
		
Site		
A	6.5	1.3
B	2.1	3.8
C	4.7	0.8
D	1.1	6.2
E	5.3	2
F	1.4	6.4
G	5	2.1
H	--	6.6
I	4.9	2.2
J	1.1	7.2

K	5.1	2.7
---	-----	-----

(6 marks)

Q5.

a) Define the following terms; Aquifer; Permeability , Porosity **(6 marks)**

b) With aid of a sketch explain the subsurface zones related to movement of rainwater **(8 marks)**

c) Explain how a double-mass curve can be used to test the inconsistencies of a rain gauge.

(6 marks)