TECHNICAL UNIVERSITY OF MOMBASA

FACULTY OF ENGINEERING & TECHNOLOGY

DEPARTMENT OF BUILDING & CIVIL ENGINEERING

UNIVERSITY EXAMINATIONS

SEPT. 2017 SERIES

DIPLOMA IN ARCHITECTURE

DA.14.S 17no YR II SEM II

SPECIAL SUPPLEMENTARY EXAMINATIONS

EAR 2205 BUILDING ENVIRONMENTAL SCIENCE II: LIGHTING DESIGN

2 HOURS

INSTRUCTIONS

- (i) You should have the following for this examination:
 - Answer booklet
 - Blue or black pen, pencil
 - Non programmable scientific calculator
- (ii) This paper consists of five questions
- (ii) Answer any three questions
- (iii) All question carry equal marks, i.e 20 each
- (iv) Maximum marks for each part of a question are shown
- (v) Use neat, large and well labeled diagrams
- (vi) Do not write on the question paper

This paper consists of 2 printed pages. Candidates should check the question paper to ascertain that all pages are printed and no questions are missing.

QUESTIONS

1. Discuss the following sub-titles:

	# ENID #	, ,
5.	Sight is a function of light and the eye. Discuss.	(20 marks)
	working plane. Point B is on the same plane but 4m away from point A. Evaluate direct illuminance at each point using the cosine law of illuminance.	(10 marks)
	b) A uniform source gives out 25133 lm is placed 3m directly above point A on a	,
1.	a) Describe the inverse square law as used in the determination of the direct component of illuminance.	(10 marks)
	e) Describe the transmission of light.	(6 marks)
	d) Explain the nature of light.	(5 marks)
	a requisite. Briefly outline the sources of light.	(5 marks)
	c) Vision is the most important channel between man and his environment, light being	
	b) Enumerate two properties of the objects that we see.	(2 marks)
3.	a) State the two types of lighting and their corresponding purposes.	(2 marks)
	ULOR = 20%	
	DLOR = 50%	
	UFu = 0.42	
	 Lower flux utilance = 0.88 	
	 B24 luminaire with maximum spacing to mounting height. Lighting design lumens (φ) for lamps = 6134 lm, 1 lamp per luminaire. 	
	iv) Whether spacing to mounting height is acceptable use of;	(5 marks)
	iii) Number of light fittings	(5 marks)
	ii) U.F.	(5 marks)
	i) Room index	(5 marks)
	Calculate:	
۷.	A room measures 20 x 9m and the light fittings are mounted on the ceiling 2.9m above the working plane. The required illuminance is 300 lux with an mf of 0.8 .	
•	A many manager 20 m on a data tight fitting a manager day the critical 2 on the con-	
	c) Wunsen system	(3 marks)
	b) Coloured light c) Munsell system	(5 marks) (5 marks)
	a) Reflection	(10 marks)