

## TECHNICAL UNIVERSITY OF MOMBASA

# FACULTY OF ENGINEERING AND TECHNOLOGY DEPARTMENT OF BUILDING & CIVIL ENGINEERING UNIVERSITY EXAMINATION FOR:

BACHELOR OF SCIENCE IN CIVIL ENGINEERING
(INSTITUTION BASED EXAMINATION)

**ECE 2304: HYDRAULICS** 

END OF SEMESTER EXAMINATION

**SERIES: MARCH 2017** 

TIME: 2 HOURS

**DATE:** 26 Mar 2017

## <u>Instructions to Candidates</u>

You should have the following for this examination

-Answer Booklet, examination pass and student ID

This paper consists of five questions.

Attempt guestion ONE (Compulsory) and any other TWO guestions.

Do not write on the question paper.

#### **QUESTION ONE (COMPULSORY)**

- a) Define an open channel. (3 Marks)
- b) A rectangular channel is 1.5m deep and 6m wide. Find the discharge through the channel when it runs full.  $S_0=1$  in 900 and C=50. (8 Marks)
- c) Water is flowing at the rate of 16.5m<sup>3</sup>/s in an earthen trapezoidal channel width 9m, water depth 1.2m and side slope 1:2. Calculate the bed slope. C=49.5. (8 Marks)
- d) An earthen channel with a 3m wide base and side slopes 1:1 carries water with a depth of 1m. The bed slope is 1 in 1600. Estimate the discharge. N=0.04. (11 Marks)

## Attempt any TWO questions OUESTION TWO

- a) Define the following terms:
  - i) Normal depth
  - ii) Turbulent flow



- iii) Specific gravity
- iv) Laminar flow
- v) Critical depth

(5 Marks)

- b) Calculate the most economical cross-section of a rectangular channel to carry 0.3m<sup>3</sup>/s when bed slope is 1 in 1000, assume Chezy's C=60. (7 Marks)
- c) A trapezoidal channel having side slopes of 1:1 and bed slope of 1 in 1200 is required to carry a discharge of 180m<sup>3</sup>/min. find the dimensions of the channel for minimum cross section. C=50. (8 Marks)

## Attempt any TWO questions QUESTION TWO

Describe the method of solving problems of non-uniform flow. (20 Marks)

## **QUESTION THREE**

- a) A rectangular section channel conveys 2.5m<sup>3</sup>/s flow with a bed slope of 0.0002. determine the best hydraulic section dimensions if:
  - i) The effective surface roughness height is 3mm
  - ii) The manning roughness coefficient is 0.014 (10 Marks)

## **QUESTION FOUR**

- a) A rectangular channel section of width 1m carries a flow of 0.3 m<sup>3</sup>/s
  - i) Assuming Chezy coefficient of 55 and slope of 0.002, estimate the depth of uniform flow.
  - ii) Assuming the efficient surface roughness height of 3.17mm and slope of 0.002, estimate the depth of uniform flow. (5 Marks)

#### **OUESTION FIVE**

- a) Outline the procedures for model analysis. (3 Marks)
- b) The discharge over a model which is reduced to 1:100 in all its dimensions is 1.5l/s. What is the corresponding discharge in the prototype? (5 Marks)
- c) Show that the resistance (R) to the motion of a sphere of diameter (D) moving with a uniform velocity (V) through a real fluid having mass density ( $\rho$ ) and viscosity ( $\mu$ ) is given by

$$R = \rho V^2 D^2 f(\frac{\mu}{\rho V D})$$

