



TECHNICAL UNIVERSITY OF MOMBASA

Faculty of Engineering and Technology

Department of BUILDING & Civil engineering

UNIVERSITY EXAMINATION FOR: BACHELOR OF SCIENCE IN CIVIL ENGINEERING

TCV 4325 and ECV 4509: HYDRAULICS II

END OF SEMESTER EXAMINATION

SERIES: JANUARY 2025

TIME: 2 HOURS

Instructions to Candidates

You should have the following for this examination

-Answer Booklet, examination pass and student ID

This paper consists of five questions.

Attempt question ONE (Compulsory) and any other TWO questions

Do not write on the question paper.

QUESTION ONE - COMPULSORY

- a) State the Newtons law of resistance (4 marks)
- b) Give the mathematical expression and state the terms. (6 marks)
- c) State 3 assumptions that the above law is based. (12 marks)
- d) A smooth plate 1m wide and 3m long moves through stationary air with a velocity of 3m/s. Determine the thickness of the boundary layer at the trailing edge. Assume for air as 0.15 stroke (5 marks)

e) Define turbulent flow.

(3 marks)

QUESTION TWO

- a) A horizontal pipe of $1\text{ mm } \phi$ is obstructed by a circular plate of $100\text{ mm } \phi$. Calculate the loss of head during the obstruction in the pipe, if the water is flowing with a velocity of 1.5 m/s in the pipe. Take C_c as 0.6 . (10 marks)
- b) Outline the two main assumptions used in handy cross method complete with diagrams. (10 marks)

QUESTION THREE

- a) A centrifugal has an external and internal impeller. The vane angle at inlet and outlet are $30^\circ \wedge 45^\circ$ respectively. If the water enters the impeller at 2.5 m/s , calculate;
- Speed of the impeller in r.p.m.
 - Work done in kN of water. (15 marks)
- b) State Manometric head. (5 marks)

QUESTION FOUR

- a) A Pelton wheel develops 2000 kW under a head of 100 m and with an overall efficiency of 85% . Calculate the ϕ of nozzle if the coefficient of velocity for the nozzle is 0.98 . (10 marks)
- b) A Pelton when having semi circular buckets and working under a head of 140 m , is running at 600 r.p.m. The discharge through the nozzle is 500 l/s and ϕ of the wheel is 600 mm . Calculate;
- Power available at the nozzle.
 - Hydraulic efficiency of the wheel if $C_v = 0.98$. (10 marks)

QUESTION FIVE

- a) A Pelton when is required to generate 3750 kW under an effective head of 400 m . Calculate the total flow in l/s and size of the jet. Assume generator efficiency 95% , $\eta_0 = 80\%$, $C_v = 0.97$. Speed ratio 0.46 . If the jet ratio is 10 , calculate the mean ϕ of runner. (15 marks)
- b) Two horizontal plates are placed 12.5 mm apart, the space between them being filled with oil of viscosity of 14 poise . Calculate the shear stress in the oil if the upper plate is moved with a of 2.5 m/s . (5 marks)