



THE MOMBASA POLYTECHNIC UNIVERSITY COLLEGE

(A Constituent College of JKUAT)

(A Centre of Excellence)

Faculty of Engineering & Technology

DEPARTMENT OF BUILDING & CIVIL ENGINEERING

CONSTRUCTION TECHNICIAN II

EBC 1115: THEORY OF DEFLECTION

END OF SEMESTER EXAMINATION

SERIES: AUGUST 2012

TIME: 2 HOURS

Instructions to Candidates:

You should have the following for this examination

- *Answer Booklet*
- *Calculator*

This paper consists of **FIVE** questions. Answer any **THREE** questions
Maximum marks for each part of a question are as shown
This paper consists of **THREE** printed pages
Question One (20 marks)

A pin-jointed shown in figure 1 is carrying a load of 600KN at C. Find the vertical deflection of C.

Take: Area of member AB = 1000mm²
Area of member AC = BC = 1500mm²
Young's Modulus (E) = 200 x 10⁶KN/m²

(20 marks)

C

Question Two (20 marks)

- a) Prove that the maximum deflection for a simply supported beam with a uniformly distributed load is $y = \frac{5WL^4}{384EI}$. **(12 marks)**
- b) A simply supported beam of span 4m is carrying a uniformly distributed load of 2KN.m over the entire span. Find the maximum slope and deflection of the beam. Take EI for the beam as 80 x 10⁹N/mm². **(8 marks)**

Question Three (20 marks)

With the aid of a sketch, show that the general differential equation is equal to $M/EI = d^2y/dx^2$. **(20 marks)**

Question Four (20 marks)

- a) State:
i) Mohr's first theorem
ii) Mohr's second theorem **(8 marks)**
- b) Using Mohr's theorem, determine:
i) Maximum slope

- ii) Maximum deflection for a simply supported beam of span 4m with a point load of 6kN at the centre. Take $EI = 4 \times 10^{12} \text{N/mm}^2$ **(12 marks)**

Question Five (20 marks)

A simply supported beam of span 14.0m carries two concentrated loads 4kN at 8m and 10kN at 12m from left as shown in figure 2. Calculate deflection under each load. Take $EI = 2.0 \times 10^{14}$. **(20 marks)**

C