



THE MOMBASA POLYTECHNIC UNIVERSITY COLLEGE

(A Constituent College of JKUAT)

(A Centre of Excellence)

Faculty of Engineering & Technology

DEPARTMENT OF BUILDING & CIVIL ENGINEERING

DIPLOMA IN CIVIL ENGINEERING (DCE 10B)

EBC 2310: ESTIMATING & COSTING OF CIVIL ENGINEERING WORKS

END OF SEMESTER EXAMINATION

SERIES: DECEMBER 2012

TIME: 3 HOURS

Instructions to Candidates:

You should have the following for this examination

- *Answer Booklet*
- *Pocket Calculator*

This paper consists of **FIVE** questions.

Answer question **ONE (COMPULSORY)** and any other **TWO** questions
Maximum marks for each part of a question are as shown
This paper consists of **THREE** printed pages

Question One

- a) Briefly explain the following:
- (i) Unit rate
 - (ii) Labour constant
 - (iii) All in labour rate
 - (iv) All in machine rate. **(8 marks)**
- b) Outline the following terms used in Estimating and Costing.
- (i) Building element
 - (ii) Cost study
 - (iii) Cost plan
 - (iv) Cost analysis
 - (v) Cost control **(5 marks)**
- c) Describe how the following design variables affect the cost of a building.
- (i) Plan shape
 - (ii) Size of the building
 - (iii) Circulation area
 - (iv) Services. **(8 marks)**
- d) Outline the **FIVE** sources of cost information. **(9 marks)**

Question Two

- a) Describe **FOUR** factors which make up:
- (i) Owning costs of a mechanical plant
 - (ii) Running cost of a mechanical plant **(8 marks)**
- b) Outline the following methods of plant depreciation:
- (i) Straight line method
 - (ii) Sum of Number of years method **(7 marks)**

Question Three

Build up a unit rate for the following using the data given in Appendix 'A'.

- a) Excavate pit for column bases commonly from ground level and not exceeding 1.50m deep (per m³) **(5 marks)**
- b) Reinforced concrete mix 1:2:4 in foundations (per m³). **(10 marks)**

Question Four

Build up a unit rate for the following using the data given in appendix 'A'.

- a) ϕ 16mm High tensile steel bars including typing wires and cover blocks (per kg). **(5 marks)**

- b) 200mm thick coral block walling in cement mortar mix 1:3 (per m²). (5 marks)
- c) Prepare and play one under coat and three finishing coats of gloss paint to timber general surfaces (per m²). (5 marks)

Appendix 'A'

Mechanical plant

Cost of backactor		Ksh. 5,000,000/-
Resale value after 5 years		Ksh 500,000/-
Interest on Capital 10% per annum		
Maintenance, repairs, insurance and Taxes @70% of annual depreciation.		
Fuel consumption 10l/hr @ 100 ksh/litre		
Operator @ Ksh 80/hr		
Banksman @ Ksh 50/hr		
Bucket Capacity	=	0.5m ³
Cycle time	=	5 minutes
Efficiency	=	85%
No of hours machine works per Annum	=	1500 hours

Labour

Skilled labour @ ksh. 80/hr
 Unskilled labour @ ksh. 50/hr

Materials

Cement 2 ksh. 700/50kg Bag
 Sand @ 1000 ksh./Tonne
 Aggregates @ 2000 ksh/Tonne
 Cement Density = 1440kg/m³
 Sand Density = 1500kg/m³
 Aggregates Density = 1600kg/m³
 ϕ
 Reinforcements 16cm bars @ ksh. 2000/12m bar
 Binding wire 2 ksh. 150/kg
 Spacer blocks @ ksh. 10 each
 Coral block size 400 x 200 x 200 2 ksh. 60 each
 Under coat paint @ ksh. 200/ litre
 Finishing gloss paint @ ksh. 300/litre

Assume any other necessary information